

IM 2702SE

MAIN SPECIFICATIONS

GENERAL

Warm-up time	25 seconds
First copy speed: BW	6.5 seconds
Continuous output speed	27 ppm
Memory: standard	4 GB (2 GB mainframe + 2 GB Smart Operation Panel)
Memory: maximum	4 GB (2 GB mainframe + 2 GB Smart Operation Panel)
ARDF capacity	100 sheets
Weight	46.5 kg
Dimensions: W x D x H	587 x 581 x 677 mm
Power source	220 - 240 V, 50 - 60 Hz

COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400%

PRINTER

Printer language	PCL5e PCL6 PostScript 3 (emulation)
Print resolution: maximum	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB2.0 Type B, USB Host 2.0
Mobile printing capability	Apple AirPrint Mopria®
Network protocol	TCP/IP
Windows® environments	Windows® 10/11, Windows® Server 2016/2019/2022/2025
Mac OS environments	Macintosh OS X v12 or later
SAP® environments	SAP® R/3® SAP® S/4®

SCANNER

Scanning: B/W	50 ipm
Scanning: full colour	50 ipm
Resolution: maximum	1,200 dpi
Bundled drivers	Network TWAIN

FAX

Compatibility	ITU-T (CCITT) G3
Transmission speed	3 seconds
Modem speed: maximum	33.6 Kbps

PAPER HANDLING

Recommended paper size	Bypass tray: Custom Size paper: Width: 90 mm - 305 mm, Length: 148 mm - 600 mm
Paper input: standard	600 sheets
Paper input: maximum	1,600 sheets
Paper output: standard	250 sheets
Paper weight: standard	Trays: 52 - 105 g/m² Bypass: 52 - 216 g/m²

ECOLOGY

Power consumption: max.	< 1,550 W
Power consumption operation: B&W	500 W

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet paper tray
2x 500-sheet paper tray
One-bin tray

OTHER OPTIONS

Fax unit
Low cabinet
ADF handle
Bypass tray cover

IM 2702SE

MAIN SPECIFICATIONS

CONSUMABLES

Toner (regular yield)	4,000 prints
Toner (high yield)	12,000 prints
Consumable yield based on 2p/j 6% coverage on A4	

For availability of models, options and software, please consult your local supplier.



Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands

+31 (0)20 5774111

ricoh-europe.com